

## 2. Convective Mass Transfer

### 2.1. Introduction

Our discussion of mass transfer in the previous chapter was limited to molecular diffusion, which is a process resulting from a concentration gradient. In system involving liquids or gases, however, it is very difficult to eliminate convection from the overall mass-transfer process.

Mass transfer by convection involves the transport of material between a boundary surface (such as solid or liquid surface) and a moving fluid or between two relatively immiscible, moving fluids.

There are two different cases of convective mass transfer:

1. Mass transfer takes place only in a single phase either to or from a phase boundary, as in sublimation of naphthalene (solid form) into the moving air.
2. Mass transfer takes place in the two contacting phases as in extraction and absorption.

### 2.2 Convective Mass Transfer Coefficient

In the study of convective heat transfer, the heat flux is connected to heat transfer coefficient as

$$Q/A = q = h(t_s - t_m) \text{ ----- (1.1)}$$

The analogous situation in mass transfer is handled by an equation of the form

$$N_A = k_c (C_{AS} - C_A) \text{ ----- (1.2)}$$

The molar flux  $N_A$  is measured relative to a set of axes fixed in space. The driving force is the difference between the concentration at the phase boundary,  $C_{AS}$  (a solid surface or a fluid interface) and the concentration at some arbitrarily defined point in the fluid medium,  $C_A$ . The convective mass transfer coefficient  $k_c$  is a function of geometry of the system and the velocity and properties of the fluid similar to the heat transfer coefficient,  $h$ .

### 2.3 Significant Parameters in Convective Mass Transfer

Dimensionless parameters are often used to correlate convective transfer data. In momentum transfer Reynolds number and friction factor play a major role. In the correlation of convective heat transfer data, Prandtl and Nusselt numbers are important. Some of the same parameters,

PREPARED BY: Dr.S.SATHISH

Page | 2

along with some newly defined dimensionless numbers, will be useful in the correlation of convective mass-transfer data.

The molecular diffusivities of the three transport process (momentum, heat and mass) have been defined as:

$$\text{Momentum diffusivity } \nu = \frac{\mu}{\rho} \text{ ----- (1.3)}$$

$$\text{Thermal diffusivity } \alpha = \frac{k}{\rho C_p} \text{ ----- (1.4)}$$

and

$$\text{Mass diffusivity } D_{AB} \text{ ----- (1.5)}$$

It can be shown that each of the diffusivities has the dimensions of  $L^2/t$ , hence, a ratio of any of the two of these must be dimensionless.

The ratio of the molecular diffusivity of momentum to the molecular diffusivity of heat (thermal diffusivity) is designated as the Prandtl Number

$$\frac{\text{Momentum diffusivity}}{\text{Thermal diffusivity}} = \text{Pr} = \frac{\nu}{\alpha} = \frac{C_p \mu}{K} \text{ ----- (1.6)}$$

The analogous number in mass transfer is Schmidt number given as

$$\frac{\text{Momentum diffusivity}}{\text{Mass diffusivity}} = \text{Sc} = \frac{\nu}{D_{AB}} = \frac{\mu}{\rho D_{AB}} \text{ ----- (1.7)}$$

The ratio of the molecular diffusivity of heat to the molecular diffusivity of mass is designated the Lewis Number, and is given by

$$\frac{\text{Thermal diffusivity}}{\text{Mass diffusivity}} = \text{Le} = \frac{\alpha}{D_{AB}} = \frac{k}{\rho C_p D_{AB}} \text{ ----- (1.8)}$$

Lewis number is encountered in processes involving simultaneous convective transfer of mass and energy.

Let us consider the mass transfer of solute A from a solid to a fluid flowing past the surface of the solid. The concentration and velocity profile is depicted. For such a case, the mass transfer between the solid surface and the fluid may be written as

$$N_A = k_c (C_{A_s} - C_{A_\infty}) \text{ ----- (1 a)}$$

Since the mass transfer at the surface is by molecular diffusion, the mass transfer may also be described by

$$N_A = -D_{AB} \left. \frac{dC_A}{dy} \right|_{y=0} \text{ ----- (1.9)}$$

When the boundary concentration,  $C_{A_s}$  is constant, equation (9) may be written as

$$N_A = -D_{AB} \left. \frac{d(C_A - C_{A_s})}{dy} \right|_{y=0} \text{ ----- (1.10)}$$

Equation (4.1a) and (4.10) may be equated, since they define the same flux of component A leaving the surface and entering the fluid

$$k_c (C_{A_s} - C_{A_\infty}) = -D_{AB} \left. \frac{d(C_A - C_{A_s})}{dy} \right|_{y=0} \text{ ----- (1.11)}$$

This relation may be rearranged into the following form:

$$\frac{k_c}{D_{AB}} = - \left. \frac{d(C_A - C_{A_s})/dy}{(C_A - C_{A_\infty})} \right|_{y=0} \text{ ----- (1.12)}$$

Multiplying both sides of equation(4.12) by a characteristic length, L we obtain the following dimensionless expression:

$$\frac{k_c L}{D_{AB}} = - \left. \frac{d(C_A - C_{A_s})/dy}{(C_{A_s} - C_{A_\infty})/L} \right|_{y=0} \text{ ----- (1.13)}$$

The right hand side of equation (4.13) is the ratio of the concentration gradient at the surface to an overall or reference concentration gradient; accordingly, it may be considered as the ratio of molecular mass-transport resistance to the convective mass-transport resistance of the fluid. This ratio is generally known as the Sherwood number,  $Sh$  and analogous to the Nusselt number  $Nu$ , in heat transfer.

## 2.4 Application of Dimensionless Analysis to Mass Transfer

One of the method of obtaining equations for predicting mass-transfer coefficients is the use of dimensionless analysis. Dimensional analysis predicts the various dimensionless parameters which are helpful in correlating experimental data.

There are two important mass transfer processes, which we shall consider, the transfer of mass into a stream flowing under forced convection and the transfer of mass into a phase which is moving as the result of natural convection associated with density gradients.

## 2.5 Transfer into a stream flowing under forced convection

Consider the transfer of mass from the walls of a circular conduit to a fluid flowing through the conduit. The mass transfer is due to the concentration driving force  $C_{As} - C_A$ .

These variables include terms descriptive of the system geometry, the flow and fluid properties and the quantity of importance,  $k_c$ .

By the Buckingham method of grouping the variables, the number of dimensionless  $\pi$  groups is equal to the number of variables minus the number of fundamental dimensions. Hence the number of dimensionless group for this problem will be three.

With  $D_{AB}$ ,  $\rho$  and  $D$  as the core variables, the three  $\pi$  groups to be formed are

$$\pi_1 = D_{AB}^a \rho^b D^c k_c \text{ ----- (1.14)}$$

$$\pi_2 = D_{AB}^d \rho^e D^f g \text{ ----- (1.15)}$$

and  $\pi_3 = D_{AB}^g \rho^h D^i \mu \text{ ----- (1.16)}$

Substituting the dimensions for  $\pi$ ,

PREPARED BY: Dr.S.SATHISH

Page | 5

$$\pi_1 = D_{AB}^a \rho^b D^c k_c \text{ ----- (1.17)}$$

$$1 = \left(\frac{L^2}{t}\right)^a \left(\frac{M}{L^3}\right)^b (L)^c \left(\frac{L}{t}\right) \text{ ----- (1.18)}$$

Equating the exponents of the fundamental dimensions on both sides of the equation, we have

$$L: \quad 0 = 2a - 3b + c + 1$$

$$t: \quad 0 = -a - 1$$

$$M: \quad 0 = b$$

Solving these equations,

$$a = -1, \quad b = 0 \quad \text{and} \quad c = 1$$

Thus  $\pi_1 = \frac{k_c D}{D_{AB}}$  which is the Sherwood number.

The other two  $\pi$  groups could be determined in the same manner, yielding

$$\pi_2 = \frac{D v}{D_{AB}} \text{ ----- (1.19)}$$

$$\text{and } \pi_3 = \frac{\mu}{\rho D_{AB}} = S_c \text{ ----- (1.20)}$$

which is termed as Schmidt Number

Dividing  $\pi_2$  by  $\pi_3$ , we get

$$\frac{\pi_2}{\pi_3} = \left(\frac{D v}{D_{AB}}\right) \Bigg/ \left(\frac{\mu}{\rho D_{AB}}\right) = \frac{D v \rho}{\mu} = \text{Re} \text{ ----- (1.21)}$$

which is the Reynolds Number

PREPARED BY: Dr.S.SATHISH

Page | 6

The result of the dimensional analysis of mass transfer by forced convection in a circular conduit indicates that a correlating relation could be of the form,

$$Sh = \psi (Re, Sc) \text{ ----- (1.22)}$$

Which is analogous to the heat transfer correlation

$$Nu = \psi (Re, Pr) \text{ ----- (1.23)}$$

## 2.6 Transfer into a phase whose motion is due to Natural Convection

Natural convection currents develop if there exists any variation in density within the fluid phase. The density variation may be due to temperature differences or to relatively large concentration differences.

In the case of natural convection involving mass transfer from a vertical plane wall to an adjacent fluid, the variables of importance are listed in the table (4.2)

**Table (4.2)**

According to Buckingham theorem, there will be three dimensionless groups. Choosing  $D_{AB}$ ,  $L$  and  $\mu$  as the core variables, the  $\pi$  groups to be formed are

$$\pi_1 = D_{AB}^a L^b \mu^c k_c \text{ ----- (4.24)}$$

$$\pi_2 = D_{AB}^d L^e \mu^f \rho \text{ ----- (4.25)}$$

and  $\pi_3 = D_{AB}^g L^h \mu^i g \Delta \rho_A \text{ ----- (4.26)}$

Solving for the dimensionless groups, we obtain

$$\pi_1 = \frac{k_c L}{D_{AB}} = Nu, \text{ the Nusselt number ----- (4.27)}$$

$$\pi_2 = \frac{\rho D_{AB}}{\mu} = \frac{1}{Sc}, \text{ the reciprocal of Schmidt number ----- (4.28)}$$

$$\text{and } \pi_3 = \frac{L^3 g \Delta \rho_A}{\mu D_{AB}} \text{ ----- (4.29)}$$

With the multiplication of  $\pi_2$  and  $\pi_3$ , we obtain a dimensionless parameter analogous to the Grashof number in heat transfer by natural convection

$$\begin{aligned} \pi_2 \pi_3 &= \left( \frac{\rho D_{AB}}{\mu} \right) \left( \frac{L^3 g \Delta \rho_A}{\mu D_{AB}} \right) \\ &= \frac{L^3 \rho g \Delta \rho_A}{\mu^2} = Gr_{AB} \text{ ----- (4.30)} \end{aligned}$$

The result of the dimensional analysis of mass transfer by natural convection indicates that a correlating relation could be of the form,

$$Sh = \psi (Gr_{AB}, Sc) \text{ ----- (4.31)}$$

## 2.7 Analysis among Mass, Heat and Momentum Transfer

Analogies among mass, heat and momentum transfer have their origin either in the mathematical description of the effects or in the physical parameters used for quantitative description.

To explore those analogies, it could be understood that the diffusion of mass and conduction of heat obey very similar equations. In particular, diffusion in one dimension is described by the Fick's Law as

$$J_A = -D_{AB} \frac{dC_A}{dz} \text{ ----- (4.32)}$$

Similarly, heat conduction is described by Fourier's law as

$$q = -k \frac{dT}{dz} \text{ ----- (4.33)}$$

Where  $k$  is the thermal conductivity.

The similar equation describing momentum transfer as given by Newton's law is

$$\tau = -\mu \frac{dv}{dz} \text{ ----- (4.34)}$$

Where  $\tau$  is the momentum flux (or shear stress) and  $\mu$  is the viscosity of fluid.

At this point it has become conventional to draw an analogy among mass, heat and momentum transfer. Each process uses a simple law combined with a mass or energy or momentum balance.

In this section, we shall consider several analogies among transfer phenomenon which has been proposed because of the similarity in their mechanisms. The analogies are useful in understanding the transfer phenomena and as a satisfactory means for predicting behaviour of systems for which limited quantitative data are available.

The similarity among the transfer phenomena and accordingly the existence of the analogies require that the following five conditions exist within the system

1. The physical properties are constant
2. There is no mass or energy produced within the system. This implies that there is no chemical reaction within the system
3. There is no emission or absorption of radiant energy.
4. There is no viscous dissipation of energy.
5. The velocity profile is not affected by the mass transfer. This implies there should be a low rate of mass transfer.

### 2.7.1 Reynolds Analogy

The first recognition of the analogous behaviour of mass, heat and momentum transfer was reported by Osborne Reynolds in 1874. Although his analogy is limited in application, it served as the base for seeking better analogies.

Reynolds postulated that the mechanisms for transfer of momentum, energy and mass are identical. Accordingly,



$$\frac{k_c}{v_\infty} = \frac{h}{\rho v_\infty C_p} = \frac{f}{2} \text{-----} (4.35)$$

Here h is heat transfer coefficient

f is friction factor

$v_\infty$  is velocity of free stream

The Reynolds analogy is interesting because it suggests a very simple relation between different transport phenomena. This relation is found to be accurate when Prandtl and Schmidt numbers are equal to one. This is applicable for mass transfer by means of turbulent eddies in gases. In this situation, we can estimate mass transfer coefficients from heat transfer coefficients or from friction factors.

### 2.7.2 Chilton – Colburn Analogy

Because the Reynold's analogy was practically useful, many authors tried to extend it to liquids. Chilton and Colburn, using experimental data, sought modifications to the Reynold's analogy that would not have the restrictions that Prandtl and Schmidt numbers must be equal to one. They defined for the j factor for mass transfer as

$$j_D = \frac{k_c}{v_\infty} (Sc)^{2/3} \text{-----} (4.36)$$

The analogous j factor for heat transfer is

$$j_H = St Pr^{2/3} \text{-----} (4.37)$$

where St is Stanton number =  $\frac{Nu}{Re Pr} = \frac{h}{\rho v_\infty C_p}$

Based on data collected in both laminar and turbulent flow regimes, they found

$$j_D = j_H = \frac{f}{2} \text{-----} (4.38)$$

This analogy is valid for gases and liquids within the range of  $0.6 < Sc < 2500$  and  $0.6 < Pr < 100$ .

PREPARED BY: Dr.S.SATHISH

Page | 10

The Chilton-Colburn analogy has been observed to hold for many different geometries for example, flow over flat plates, flow in pipes, and flow around cylinders.

13. A stream of air at 100 kPa pressure and 300 K is flowing on the top surface of a thin flat sheet of solid naphthalene of length 0.2 m with a velocity of 20 m/sec. The other data are:

Mass diffusivity of naphthalene vapor in air =  $6 * 10^{-6} \text{ m}^2/\text{sec}$

Kinematic viscosity of air =  $1.5 * 10^{-5} \text{ m}^2.\text{sc}$

Concentration of naphthalene at the air-solid naphthalene interface =  $1 * 10^{-5} \text{ kmol/m}^3$

**Calculate:**

- the overage mass transfer coefficient over the flat plate
- the rate of loss of naphthalene from the surface per unit width

Note: For heat transfer over a flat plate, convective heat transfer coefficient for laminar flow can be calculated by the equation.

$$Nu = 0.664 Re_L^{1/2} Pr^{1/3}$$

you may use analogy between mass and heat transfer.

**Solution:**

Given: Correlation for heat transfer

$$Nu = 0.664 Re_L^{1/2} Pr^{1/3}$$

The analogous relation for mass transfer is

$$Sh = 0.664 Re_L^{1/2} Sc^{1/3} \text{ -----(1)}$$

where

Sh = Sherwood number =  $kL/D_{AB}$

$Re_L$  = Reynolds number =  $Lv\rho/\mu$

Sc = Schmidt number =  $\mu / (\rho D_{AB})$

k = overall mass transfer coefficient

L = length of sheet

$D_{AB}$  = diffusivity of A in B

PREPARED BY: Dr.S.SATHISH

Page | 11

$v$  = velocity of air

$\mu$  = viscosity of air

$\rho$  = density of air, and

$\mu/\rho$  = kinematic viscosity of air.

Substituting for the known quantities in equation (1)

$$\frac{k(0.2)}{6 * 10^{-6}} = 0.664 \left( \frac{(0.2)(20)}{1.5 * 10^{-5}} \right)^{1/2} \left( \frac{1.5 * 10^{-5}}{6 * 10^{-6}} \right)^{1/3}$$

$$k = 0.014 \text{ m/sec}$$

$$\begin{aligned} \text{Rate of loss of naphthalene} &= k (C_{Ai} - C_{A\infty}) \\ &= 0.014 (1 * 10^{-5} - 0) = 1.4024 * 10^{-7} \text{ kmol/m}^2 \text{ sec} \end{aligned}$$

$$\begin{aligned} \text{Rate of loss per meter width} &= (1.4024 * 10^{-7}) (0.2) = 2.8048 * 10^{-8} \text{ kmol/m.sec} \\ &= 0.101 \text{ gmol/m.hr.} \end{aligned}$$

## 2.8 Convective Mass Transfer Correlations

Extensive data have been obtained for the transfer of mass between a moving fluid and certain shapes, such as flat plates, spheres and cylinders. The techniques include sublimation of a solid, vapourization of a liquid into a moving stream of air and the dissolution of a solid into water.

These data have been correlated in terms of dimensionless parameters and the equations obtained are used to estimate the mass transfer coefficients in other moving fluids and geometrically similar surfaces.

### 2.8.1 Flat Plate

From the experimental measurements of rate of evaporation from a liquid surface or from the sublimation rate of a volatile solid surface into a controlled air-stream, several correlations are available. These correlation have been found to satisfy the equations obtained by theoretical analysis on boundary layers,

$$Sh = 0.664 Re_L^{1/2} Sc^{1/3} \text{ (laminar) } Re_L < 3 * 10^5 \text{ ----- (4.39)}$$

$$Sh = 0.036 Re_L^{0.8} Sc^{1/3} \text{ (turbulent) } Re_L > 3 * 10^5 \text{ ----- (4.40)}$$

Using the definition of  $j$  factor for mass transfer on equation (4.39) and (4.40) we obtain

$$j_D = 0.664 \text{Re}_L^{-1/2} \text{ (laminar) } \text{Re}_L < 3 * 10^5 \text{ ----- (4.41)}$$

$$j_D = 0.037 \text{Re}_L^{-0.2} \text{ (turbulent) } \text{Re}_L > 3 * 10^5 \text{ ----- (4.42)}$$

These equations may be used if the Schmidt number in the range  $0.6 < Sc < 2500$ .

7. If the local Nusselt number for the laminar boundary layer that is formed over a flat plate is

$$Nu_x = 0.332 \text{Re}_x^{1/2} \text{Sc}^{1/3}$$

Obtain an expression for the average film-transfer coefficient  $\bar{k}_c$ , when the Reynolds number for the plate is

- a)  $\text{Re}_L = 100\,000$
- b)  $\text{Re}_L = 1500\,000$

The transition from laminar to turbulent flow occurs at  $\text{Re}_x = 3 * 10^5$ .

**Derivation:**

$$\text{By definition: } \bar{k}_c = \frac{\int_0^L k_c dx}{\int_0^L dx}$$

$$\text{and } Nu_x = \frac{k_c x}{D_{AB}}; \quad \text{Re}_x = \frac{x v \rho}{\mu}; \quad \text{Sc} = \frac{\mu}{\rho D_{AB}};$$

For  $\text{Re}_L = 100\,000$ ; (which is less than the Reynolds number corresponding to Transition value of  $3 * 10^5$ )

$$\bar{k}_c = \frac{\int_0^L 0.332 \left( \frac{x v \rho}{\mu} \right)^{1/2} (\text{Sc})^{1/3} \frac{D_{AB}}{x} dx}{L}$$

PREPARED BY: Dr.S.SATHISH

Page | 13

$$= \frac{0.332 (Sc)^{1/3} \left(\frac{v \rho}{\mu}\right)^{1/2}}{L} D_{AB} \int_0^L \frac{dx}{x^{1/2}}$$

$$= \frac{0.332}{\frac{1}{2}L} Sc^{1/3} \left(\frac{v \rho}{\mu}\right)^{1/2} D_{AB} \left[x^{1/2}\right]_0^L$$

$$(i.e.) \frac{\bar{k}_c L}{D_{AB}} = 0.664 Re_L^{1/2} Sc^{1/3} \quad [\text{answer (a)}]$$

For  $Re_L = 1500000 (> 3 * 10^5)$ 

$$\bar{k}_c = D_{AB} \frac{\left( \int_0^{L_t} 0.332 Re_x^{1/2} Sc^{1/3} \frac{dx}{x} + \int_{L_t}^L 0.0292 Re_x^{4/5} Sc^{1/3} \frac{dx}{x} \right)}{L}$$

where  $L_t$  is the distance from the leading edge of the plane to the transition point where  $Re_x = 3 * 10^5$ .

$$\bar{k}_c = D_{AB} \frac{\left( 0.332 Sc^{1/3} \left(\frac{v \rho}{\mu}\right)^{1/2} \int_0^{L_t} \frac{dx}{x^{1/2}} + 0.0292 Sc^{1/3} \left(\frac{v \rho}{\mu}\right)^{4/5} \int_{L_t}^L \frac{dx}{x^{1/5}} \right)}{L}$$

$$\frac{\bar{k}_c L}{D_{AB}} = 0.664 Re_t^{1/2} Sc^{1/3} + \frac{0.0292}{4/5} Sc^{1/3} \left[x^{4/5}\right]_{L_t}^L \left(\frac{v \rho}{\mu}\right)^{4/5}$$

$$= 0.664 Re_t^{1/2} Sc^{1/3} + 0.0365 Sc^{1/3} \left(Re_L^{4/5} - Re_t^{4/5}\right)$$

$$\frac{\bar{k}_c L}{D_{AB}} = 0.664 Re_t^{1/2} Sc^{1/3} + 0.0365 Re_L^{4/5} Sc^{1/3} - 0.0365 Re_t^{4/5} Sc^{1/3}$$

here  $Re_t = 3 * 10^5$ 

### 2.8.2 Single Sphere

PREPARED BY: Dr.S.SATHISH

Page | 14

Correlations for mass transfer from single spheres are represented as addition of terms representing transfer by purely molecular diffusion and transfer by forced convection, in the form

$$Sh = Sh_o + C Re^m Sc^n \text{ ----- (4.43)}$$

Where C, m and n are constants, the value of n is normally taken as 1/3

For very low Reynold's number, the Sherwood number should approach a value of 2. This value has been derived in earlier sections by theoretical consideration of molecular diffusion from a sphere into a large volume of stagnant fluid. Therefore the generalized equation becomes

$$Sh = 2 + C Re^m Sc^{1/3} \text{ ----- (4.44)}$$

For mass transfer into liquid streams, the equation given by Brain and Hales

$$Sh = \left(4 + 1.21 Pe_{AB}^{2/3}\right)^{1/2} \text{ ----- (4.45)}$$

correlates the data that are obtained when the mass transfer Peclet number,  $Pe_{AB}$  is less than 10,000. This Peclet number is equal to the product of Reynolds and Schmidt numbers (i.e.)

$$Pe_{AB} = Re Sc \text{ ----- (4.46)}$$

For Peclet numbers greater than 10,000, the relation given by Levich is useful

$$Sh = 1.01 Pe_{AB}^{1/3} \text{ ----- (4.47)}$$

The relation given by Froessling

$$Sh = 2 + 0.552 Re^{1/2} Sc^{1/3} \text{ ----- (4.48)}$$

correlates the data for mass transfer into gases for at Reynold's numbers ranging from 2 to 800 and Schmidt number ranging 0.6 to 2.7.

For natural convection mass transfer the relation given by Schutz

$$Sh = 2 + 0.59 (Gr_{AB} Sc)^{1/4} \text{ ----- (4.49)}$$

is useful over the range

PREPARED BY: Dr.S.SATHISH

Page | 15

$$2 * 10^8 < Gr_{AB} Sc < 1.5 * 10^{10}$$

6. The mass flux from a 5 cm diameter naphthalene ball placed in stagnant air at 40°C and atmospheric pressure, is  $1.47 * 10^{-3}$  mol/m<sup>2</sup>. sec. Assume the vapor pressure of naphthalene to be 0.15 atm at 40°C and negligible bulk concentration of naphthalene in air. If air starts blowing across the surface of naphthalene ball at 3 m/s by what factor will the mass transfer rate increase, all other conditions remaining the same?

For spheres :

$$Sh = 2.0 + 0.6 (Re)^{0.5} (Sc)^{0.33}$$

Where Sh is the Sherwood number and Sc is the Schmids number. The viscosity and density of air are  $1.8 * 10^{-5}$  kg/m.s and  $1.123$  kg/m<sup>3</sup>, respectively and the gas constant is  $82.06$  cm<sup>3</sup>. atm/mol.K.

**Calculations:**

$$Sh = \frac{k_c L}{D_{AB}} \text{ where } L \text{ is the characteristic dimension for sphere } L = \text{Diameter.}$$

$$Sc = \frac{\mu}{\rho D_{AB}}$$

$$Re = \frac{D V \rho}{\mu}$$

$$\text{Mass flux, } N_A = K_c \Delta c \text{ -----(1)}$$

$$Sh = 2.0 + 0.6 (Re)^{0.5} (Sc)^{0.33}$$

$$\frac{k_c D}{D_{AB}} = 2.0 + 0.6 \left( \frac{D V \rho}{\mu} \right)^{0.5} \left( \frac{\mu}{\rho D_{AB}} \right)^{0.33} \text{ ----- (2)}$$

$$\text{also } N = K_G \Delta \bar{p}_A$$

$$\text{Therefore } \frac{k_c}{RT} = K_G$$

Given:

PREPARED BY: Dr.S.SATHISH

Page | 16

$$N = 1.47 * 10^{-3} \frac{\text{mol}}{\text{m}^2 \cdot \text{sec}} = \frac{K_c}{RT} \Delta \bar{p}_A$$

$$\frac{k_c}{RT} \left( \frac{0.15}{1} - 0 \right) = 1.47 * 10^{-3} * 10^{-4} \frac{\text{mol}}{\text{cm}^2 \cdot \text{sec}}$$

$$k_c = \frac{1.47 * 10^{-7}}{0.15} * 82.06 * (273 + 40)$$

$$= 0.0252 \text{ cm/sec}$$

$$k_c = 2.517 * 10^{-4} \text{ m/sec} \text{ -----(3)}$$

**Estimation of  $D_{AB}$ :**

From (2),

$$\frac{2.517 * 10^{-4} * 5 * 10^{-2}}{D_{AB}} = 2 \quad (\text{since } v = 0)$$

Therefore  $D_{AB} = 6.2925 * 10^{-6} \text{ m}^2/\text{sec}$ .

And

$$\frac{k_c * 5 * 10^{-2}}{6.2925 * 10^{-6}} = 2 + 0.6 \left( \frac{5 * 10^{-2} * 3 * 1.123}{1.8 * 10^{-5}} \right)^{0.5} \left( \frac{1.8 * 10^{-5}}{1.123 * 6.2925 * 10^{-6}} \right)^{0.33}$$

$$7946 k_c = 2 + 0.6 * (96.74) * (1.361)$$

$$k_c = 0.0102 \text{ m/sec.} \text{ ----- (4)}$$

$$\frac{(4)}{(3)} \Rightarrow \frac{N_{A2}}{N_{A1}} = \frac{0.0102}{2.517 * 10^{-4}} = 40.5$$

Therefore, rate of mass transfer increases by 40.5 times the initial conditions.

### 2.8.3 Single Cylinder



PREPARED BY: Dr.S.SATHISH

Page | 17

Several investigators have studied the rate of sublimation from a solid cylinder into air flowing normal to its axis. Bedingfield and Drew correlated the available data in the form

$$\frac{k_G P Sc^{0.56}}{G_m} = 0.281 (Re')^{-0.4} \text{----- (4.50)}$$

which is valid for  $400 < Re' < 25000$

and  $0.6 < Sc < 2.6$

Where  $Re'$  is the Reynold's number in terms of the diameter of the cylinder,  $G_m$  is the molar mass velocity of gas and  $P$  is the pressure.

#### 2.8.4 Flow Through Pipes

Mass transfer from the inner wall of a tube to a moving fluid has been studied extensively. Gilliland and Sherwood, based on the study of rate of vapourization of nine different liquids into air given the correlation

$$Sh \frac{p_{B,lm}}{P} = 0.023 Re^{0.83} Sc^{0.44} \text{----- (4.51)}$$

Where  $p_{B,lm}$  is the log mean composition of the carrier gas, evaluated between the surface and bulk stream composition.  $P$  is the total pressure. This expression has been found to be valid over the range

$$\begin{aligned} 2000 < Re < 35000 \\ 0.6 < Sc < 2.5 \end{aligned}$$

Linton and Sherwood modified the above relation making it suitable for large ranges of Schmidt number. Their relation is given as

$$Sh = 0.023 Re^{0.83} Sc^{1/3} \text{----- (4.52)}$$

and found to be valid for

$$\begin{aligned} 2000 < Re < 70000 \\ \text{and } 1000 < Sc < 2260 \end{aligned}$$

8. A solid disc of benzoic acid 3 cm in diameter is spin at 20 rpm and 25°C. Calculate the rate of dissolution in a large volume of water. Diffusivity of benzoic acid in water is  $1.0 * 10^{-5}$  cm<sup>2</sup>/sec, and solubility is 0.003 g/cc. The following mass transfer correlation is applicable:

PREPARED BY: Dr.S.SATHISH

Page | 18

$$Sh = 0.62 Re^{1/2} Sc^{1/3}$$

Where  $Re = \frac{D^2 \omega \rho}{\mu}$  and  $\omega$  is the angular speed in radians/time.

**Calculations:**

$$\text{Dissolution rate} = N_A S \quad \text{-----(1)}$$

Where  $N_A$  = mass flux, and  
 $S$  = surface area for mass transfer

$$N_A = k_c (C_{As} - C_{A\infty}) \quad \text{----- (2)}$$

Where  $C_{As}$  is the concentration of benzoic acid in water at the surface of the disc.  
 $C_{A\infty}$  is the concentration benzoic acid in water far from the surface of the disc.

**Given:**

$$Sh = 0.62 Re^{1/2} Sc^{1/3}$$

$$\text{(i.e.) } \frac{k_c D}{D_{AB}} = 0.62 \left( \frac{D^2 \omega \rho}{\mu} \right)^{1/2} \left( \frac{\mu}{\rho D_{AB}} \right)^{1/3} \quad \text{----- (3)}$$

$$1 \text{ rotation} = 2 \pi \text{ radian}$$

$$\begin{aligned} \text{Therefore 20 rotation per minute} &= 20 * 2 \pi \text{ radian/min} \\ &= \frac{20}{60} * 2 \pi \text{ radian/sec} \end{aligned}$$

$$\text{For water } \rho = 1 \text{ g/cm}^3 \quad \mu = 1 \text{ centipoise} = 0.01 \text{ g/cm.sec.}$$

From (3),

$$\begin{aligned} k_c &= 0.62 D_{AB} \left( \frac{\omega \rho}{\mu} \right)^{1/2} \left( \frac{\mu}{\rho D_{AB}} \right)^{1/3} \\ &= 0.62 * 1.0 * 10^{-5} * \left( \frac{(40 \pi / 60) * 1}{0.01} \right)^{1/2} \left( \frac{0.01}{1 * 1.0 * 10^{-5}} \right)^{1/3} \\ &= 8.973 * 10^{-4} \text{ cm/sec.} \end{aligned}$$

PREPARED BY: Dr.S.SATHISH

Page | 19

From (2),

$$\begin{aligned} N_A &= 8.973 * 10^{-4} (0.003 - 0) \\ &= 2.692 * 10^{-6} \text{ g/cm}^2 \cdot \text{sec} \end{aligned}$$

From (1),

$$\begin{aligned} N_A S &= N_A * (2\pi r^2) \\ &= 2.692 * 10^{-6} * (2\pi * 1.5^2) \\ &= 3.805 * 10^{-5} \text{ g/sec} \\ &= 0.137 \text{ g/hr.} \end{aligned}$$

### 2.9 Mass transfer between phases:

Instead of a fluid in contact with a solid, suppose we now consider two immiscible fluids, designated 1 and 2, in contact with each other. If fluid 1 has dissolved in it a substance A that is also soluble in fluid 2, then as soon as the two fluids are brought together, substance A will begin to diffuse into fluid 2. As long as the two phases remain in contact, the transport of A will continue until a condition of equilibrium is reached.

The situation discussed here occurs in a variety of engineering processes such as gas absorption, stripping, and in liquid – liquid extraction. In all these separation processes, two immiscible fluids are brought into contact and one or more components are transferred from one fluid phase to the other.

In the system of fluids 1 and 2 with A, the transported component, the concentration gradients in the region of the interface between the two fluids are illustrated in figure. Concentration  $C_{A1}$  and  $C_{A2}$  are the bulk phase concentrations

in fluids 1 and 2, respectively,  $C_{Ai}$  is the concentration of A at the interface, and  $N_A$  is the molar flux of A. For steady state conditions, we can define the flux of A as

$$N_A = k_{c1} (C_{A1} - C_{Ai}) = k_{c2} (C_{Ai} - C_{A2}) = K_c (C_{A1} - C_{A2}) \quad (1)$$

where  $k_c$  = individual mass transfer coefficient defined in terms of the concentration difference in a single phase.

$K_c$  = overall mass transfer coefficient defined in terms of the overall difference in composition.

Equation (1) is analogous to that in heat transfer, where the individual coefficients  $h$  are related to the overall coefficient  $U$ .

From equation (1),

$$\frac{1}{k_{c1}} + \frac{1}{k_{c2}} = \frac{1}{K_c} \quad (2)$$

PREPARED BY: Dr.S.SATHISH

Page | 20

In equation (1), the potential for mass transfer is exposed in terms of composition. However, this is not always the most convenient way to express it. For example, if fluid 1 is a gas and fluid 2 a liquid, as in gas absorption, the potential in gas phase is often expressed in terms of partial pressures, while that in the liquid phase may be expressed in terms of concentrations. The expression for the molar flux is then written for the individual phases as:

$$N_A = K_p (P_{AG} - P_{Ai}) = K_c (C_{Ai} - C_{AL}) \quad \text{_____ (3)}$$

where

$k_p$  = individual mass transfer coefficient for the gas phase with the potential defined in terms of partial pressures.

$P_{AG}$ ,  $C_{AL}$  = partial pressure and concentration of A in the bulk gas and liquid phases, respectively.

$P_{Ai}$ ,  $C_{Ai}$  = partial pressure and concentration of A, respectively, at the interface.

At the interface, it is usually assumed the two phases are in equilibrium. This means that  $P_{Ai}$  and  $C_{Ai}$  are related by an equilibrium relationship such as 'Henry's law':

$$P_{Ai} = H C_{Ai} \quad \text{_____ (4)}$$

where H is Henry's law constant.

The flux  $N_A$  can also be expressed in terms of overall mass transfer coefficients as,

$$N_A = K_p (P_{AG} - P_{AE}) = K_c (C_{AE} - C_{AL}) \quad \text{_____ (5)}$$

where

$K_p$  = overall mass transfer coefficient with the overall potential defined in terms of partial pressures.

$K_c$  = overall mass transfer coefficient with the overall potential defined in terms of concentrations.

$P_{AE}$ ,  $C_{AE}$  = equilibrium composition.

$P_{AE}$  is related to the bulk liquid composition  $C_{AL}$  AS

$$P_{AE} = H C_{AL} \quad \text{_____ (6)}$$

$$\text{similarly, } C_{AE} = \frac{P_{AG}}{H} \quad \text{_____ (7)}$$

The relationship between the individual and overall coefficients is readily obtained through the use of equations (3) to (7) as

$$\frac{1}{K_p} = \frac{1}{k_p} + \frac{H}{k_c} = \frac{H}{K_c} \quad \text{_____ (8)}$$

In many system, mass transfer resistance is mainly in one phase. For example, gases such as nitrogen and oxygen do not dissolve much in liquids. Their Henry's law constant H is very large, thus  $K_c \approx k_c$  is a good approximation. In this case, the liquid phase controls the mass transfer press since mass transfer is slowest there.

